	I	<b>8</b> 132	SUF 241 W	er Stre	ET		<i>Phone: 818-485-0500 FAX: 818-485-0540 Outside CA: 1-800-RRRIVET</i> www.hansonrivet.com														
MasterCa	ard		PN	JE	:U/	MA7	ΓΙ		R	I\	VE	T	SQ							VISA	
MODEL	STANDARD YOKES*		RIVET DIA CAPACI SOLID SOLII		ES** TUBULAR	APPROXIMATE RIVET LENGTH CAPACITY	MODEL	STANDA YOKES	S*	CAPACITI		ES** A RI TUBULAR	APPROXIMATE RIVET LENGTH CAPACITY	MODEL			SOLID	RIVET DIAMET CAPACITIES* SOLID SOLID TU		APPROXIMATE RIVET LENGTH CAPACITY	
3000CS	3" 3" 3" 6"	3.25" 4.25" 5.25" 3.50"	alum. 5/32"	STEEL 1/8"	3/16"	1.50" 2.50" 3.50" 1.75"	8000CS		5"	ALUM.	STEEL 3/16"	STEEL 5/16"	4.25"	8000CSA	9.5" 12.5"	5" 5" 5.75"	ацим. 1/4"	3/16"	STEEL 5/16"	2.00"	
6000CS	3" 3" 3" 6"	3.25" 4.25" 5.25" 3.50"	3/16"	5/32"	1/4"	1.50" 2.50" 3.50" 1.75"	15KCS	6"	5"	3/8"	5/16"	3/8"	4.25"	15KCSA	9.5" 12.5" 24"	5" 5" 5.75"	3/8"	5/16"	3/8"	2.00"	
MODE			NDARD KES* CLOSED GAP		RIVET SOLIE ALUMIN	SOL	ETER CAPACITIE SOLID TU STEEL		Rľ	APPROXIMATE RIVET LENGTH CAPACITY			PEDEST			et/				19	
3000A	s	1.50" 2.25" 3.00"	.875 1.12 .937	5" 2"	5/32" 1/8" 3/32"	1/8 3/3 1/1	." 2" 6"	3/16" 5/32" 1/8"		.62 .87 .68	0" 7"	1 R	PEDESTAL FOR ALL STATIONARY TOOLS Our pedestal is ideal for Stationary Tools Model 8000CS and 15KCS. It comes complete with an Air-Filter-Lubricator- Regulator unit. Considering the heavy duty welded steel								
6000A	s	1.50" 2.25" 3.00" 3.50"	.875 1.12 .937 1.00	2"	7/32" 3/16" 5/32" 5/32"	5/3 9/6	2" 4"	1/4" 3/16" 3/16" 9/64"		.87 .68	625" construction and its design to maximize the versatility of these   870" tools, the pedestal adds great value to your investment.   687" (Model 15KCSA with a 24" reach pictured above.)										

See page F82-F83 for Squeezer Dies to fit these tools. \*NOTE: Other size Yokes available, call for details. \*\*NOTE: Tool capacity can very based on rivet hardness and application.

Please visit www.hansonrivet.com for a full product selection.